

Oil and Gas: Application Focus

Adsorbent Dehydration

Ensure your dehydration reliably meets your daily production quotas and environmental protection needs.

Process Description

Dehydration, the removal of water from natural gas, prevents formation of gas hydrates and subsequent fouling of critical downstream components, reduces corrosion, maximizes pipeline and process efficiencies, and protects water sensitive catalysts in refinery processes. In desiccant operations, common adsorbent materials include molecular sieves, silica gels and activated alumina.

The wet hydrocarbon gas enters the top of the adsorption tower and flows downward through the adsorbent where the water is adsorbed. The essentially dry hydrocarbon gas exits at the bottom and is ready for processing or sale. Most desiccant systems have two or more adsorption towers enabling one to be regenerated while the remaining tower(s) are in operation. Bed regeneration is accomplished by flowing heated dry gas upward so that contaminants adsorbed within the bed can be removed.

To maintain their effectiveness, desiccants must be protected from free water and liquid hydrocarbon contamination to achieve their anticipated 3 to 5 year life. Free water causes long term fracturing and dusting of the desiccant granules, while hydrocarbons burn onto the granules during regeneration, progressively reducing moisture removal capability.




Gas Plant Needs

- Achieve or exceed natural gas production quotas via reliable treatment of wet gases
- Maintain process reliability for consistency of production and minimization of downtime
- Provide consistent on-spec sales gas quality for water content
- Minimize desiccant bed degradation that can lead to premature water breakthrough
- Minimize pressure drop increase

Production Challenge/Pall Solution

Challenge	Solution
Desiccant bed degradation due to foreign material, such as glycol, amine, lube oil, corrosion inhibitors and solids, coating and plugging the pores of the adsorbent and preventing access to the large interior surface	Improve your dehydration productivity and reliability with effective liquid and solid removal upstream of the desiccant beds to protect against bed degradation and capacity loss. <ul style="list-style-type: none"> • High efficiency SepraSol™ Plus liquid/gas coalescers and Medallion™ HP liquid/gas coalescers provide 99.999% removal at 0.3 microns per the DOP test and 1 ppb downstream per the modified ANSI/CAGI-400-1999 test procedure.
Bed damage due to large ingress of liquid water, causing the bed to fracture	Protect against introduction of slugs of water by capturing these slugs upstream of the desiccant beds. <ul style="list-style-type: none"> • The SepraSol Plus liquid/gas coalescer assembly has a dual sump provision that accepts most slugs without bypass or loss of removal efficiency. • Pall's full element oleophobic treated SepraSol Plus coalescers also recover very quickly, minimizing the pressure drop across the assembly.
Damage to downstream process equipment due to entrainment of desiccant fines in the dry gas stream	Protect downstream equipment, such as compressors and catalyst beds through effective solids control downstream of the desiccant beds. <ul style="list-style-type: none"> • The DGF Dry Gas Particulate Filter removes desiccant fines and other contaminants from the dry hydrocarbon gas stream before it enters the pipeline, compressor, or catalyst bed.

Process Flow Diagram



Key Applications/Filter Recommendations (*other applications not shown*)

Application	Pall Product	Advantages	Customer Benefits
1 Desiccant bed protection	SepraSol Plus liquid/gas coalescer Medallion HP liquid/gas coalescer	Efficiently remove micron and sub-micron size liquid droplets of water and hydrocarbons that shorten desiccant life	Productivity, reliability, on-spec water content, and extended desiccant life via maintained dehydrator efficiency and capacity
2 Downstream protection	MCC 1401 style dry gas filter Profile® Coreless dry gas filter	Efficiently protect metering and downstream processes (e.g. mercury guard bed, cold box) from micron size desiccant fines	Downstream process reliability by elimination of desiccant dust

Experience Matters

Don't take our word for it. Just ask the thousands of oil and gas engineers around the world why Pall is their supplier of choice for filtration and separations solutions. Let them tell you how our extended filter life and simple maintenance protocols save them time that can be spent on value-add process improvements. Ask them about the reliability and consistent output from the Pall systems installed in their critical processes. You don't want to spend time worrying about your filters and coalescers, and we don't want you to either.

Contact Pall today and let us put our 50+ years of experience to work for you.



Fuels and Chemicals

25 Harbor Park Drive
Port Washington, New York 11050
+1 516 484 3600 telephone
+1 888 873 7255 toll free US

Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid. Products in this document may be covered by one or more patent numbers. For a complete list of Pall's patents please visit <http://www.pall.com/main/about-pall/patents.page>

© Copyright 2015 Pall Corporation. Pall, (PALL), Medallion, Profile, and SepraSol are trademarks of Pall Corporation. ® Indicates a Pall trademark registered in the USA. **Filtration. Separation. Solution.SM** and **BETTER LIVES. BETTER PLANET.** are service marks of Pall Corporation.

